

# ISO 54409 thrust ball bearings

ISO 54409 thrust ball bearings Industries and Applications ?  
We sell discount online as 28x62x80 Size (mm) well 62 Outer Diameter (mm) as cheap machinery parts.

Size (mm)	28x62x80
Bore Diameter (mm)	28
Outer Diameter (mm)	62
Width (mm)	80
D	62 mm
d	28 mm
B	80 mm
C	29 mm
B1	49.5 mm
B2	11 mm
B3	22 mm
C1	0.8 mm
d1	44 mm
G	M 24×1.5
G1	25 mm
M	8 mm
M1	4 mm
SW	14 mm
c	1 mm
r1,2 – min.	1 mm
Basic dynamic load rating – C	31.4 kN
Basic static load rating – C0	72 kN

Fatigue load limit – Pu	9 kN
Maximum dynamic radial loads – Fr	72 kN
Maximum static radial loads – F0r	102 kN
Limiting speed	1700 r/min
Mass support roller	0.815 kg
Recommended tightening torque	220 N·m
Grease fitting	NIP A3x9.5
Hexagonal nut	M 24x1.5
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
UNSPSC	31171530
Weight / Kilogram	0.911
EAN	7316571620718
Product Group	B04144
r1,2 min.	1 mm
Basic dynamic load rating C	31.4 kN
Basic static load rating C0	72 kN
Fatigue load limit Pu	9 kN
Maximum dynamic radial loads Fr max.	72 kN
Maximum static radial loads F0r max.	102 kN
Mass cam follower	0.81 kg
Lubrication adapter	AP 14