

# ISO 6036 ZZ deep groove ball bearings

Request A Quote For Your Special ISO 6036 ZZ deep groove ball bearings Needs Today! Free 50 Bore Diameter (mm) Quotes. ISO 9001 50x43x15 Size (mm) certified.

Size (mm)	50x43x15
Bore Diameter (mm)	50
Outer Diameter (mm)	43
Width (mm)	15
d	50 mm
A	43 mm
A1	15 mm
A3 – H14	3.2 mm
A5	29.5 mm
B	51.6 mm
B4	9 mm
Da – H11	101.6 mm
Db1	107 mm
Db2	116 mm
J	157 mm
H	18 mm
L	116 mm
s1	32.6 mm
T	60.6 mm
J6	127 mm
J7	20 mm
N4	2 mm

RG – 1/4-28 UNF	1/428 UNF
R1	28.5 mm
Rα	45 °
Basic dynamic load rating – C	35.1 kN
Basic static load rating – C0	23.2 kN
Fatigue load limit – Pu	0.98 kN
Limiting speed	800 r/min
Mass bearing unit	2.05 kg
Thread – G2	M10x1
Hexagonal key size for grub screw – H	5 mm
Housing material	Cast iron
Da	101.6 mm
A3	3.2 mm
N	18 mm
RG	1/4-28 UNF
Rα	45 °
Basic dynamic load rating C	35.1 kN
Basic static load rating C0	23.2 kN
Fatigue load limit Pu	0.98 kN
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Housing	FYTB 510 M/VZ033
Bearing	YARAG 210
End cover	ECY 210