

ISO 6407 deep groove ball bearings

Welcome to the ISO 6407 deep groove ball bearings 31.75 mm da online 71.999 mm Da seller.

da	31.75 mm
Da	71.999 mm
Ca	26.797 mm
A1	50.8 mm
A2	153.988 mm
S	1.984 mm
ba	24.606 mm
H	98.822 mm
H1	50.8 mm
H2	20.637 mm
J min.	142.875 mm
J max.	155.575 mm
L	190.5 mm
N1	15.875 mm
R1	23.813 mm
R2	12.7 mm
RG	1/8 NPT
PG	1/8 NPT
h	22.225 mm
Housing	SAF 507
Bearing	22207 EK
Adapter sleeve assembly	SNW 7×1.1/4
Stabilizing ring	36053-6

Taconite seal	TER 14
End plug (suffix Y)	EPR 2
Max. speed for Taconite seal	2250 r/min
P60°	18.2 kN
P90°	11.1 kN
P120°	6.67 kN
P150°	5.78 kN
P180°	7.12 kN
Pa	2.4 kN
Mass pillow block	4.15 kg
Cap bolt	2 x 3/8-16 UNC
Cap bolt recommended tightening torque	40.7 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	19.845 g