

# ISO 7002 BDT angular contact ball bearings

Find the discount ISO 7002 BDT angular contact ball bearings online you need . We offer ... 40x80x23 Size (mm) If you 40 Bore Diameter (mm) check out our large selection of ISO 7002 BDT angular contact ball bearings once .

|                               |            |
|-------------------------------|------------|
| Size (mm)                     | 40x80x23   |
| Bore Diameter (mm)            | 40         |
| Outer Diameter (mm)           | 80         |
| Width (mm)                    | 23         |
| d                             | 40 mm      |
| D                             | 80 mm      |
| B                             | 23 mm      |
| C                             | 23 mm      |
| r min.                        | 1.1 mm     |
| da min.                       | 46.5 mm    |
| Da max.                       | 73.5 mm    |
| ra max.                       | 1 mm       |
| Weight                        | 0.505 Kg   |
| Basic dynamic load rating (C) | 22.4 kN    |
| Basic static load rating (C0) | 7.40 kN    |
| (Grease) Lubrication Speed    | 7600 r/min |
| (Oil) Lubrication Speed       | 9300 r/min |
| Calculation factor (e)        | 0.33       |
| Calculation factor (Y0)       | 2.01       |
| Calculation factor (Y1)       | 1.92       |
| Bearing No.                   | 2208       |

|                   |       |
|-------------------|-------|
| r(min)            | 1.1   |
| Cr                | 22.4  |
| C0r               | 7.35  |
| Cu                | 0.46  |
| Grease lub.       | 7600  |
| Oil lub.          | 9300  |
| da(min)           | 46.5  |
| Da(max)           | 73.5  |
| ra(max)           | 1     |
| e                 | 0.33  |
| Y1                | 1.92  |
| Y2                | 2.96  |
| Y0                | 2.01  |
| (Refer.)Mass (kg) | 0.505 |