

ISO 7022 BDT angular contact ball bearings

LET OUR ISO 7022 BDT angular contact ball bearings EXPERTS GET YOU THE 28 mm d PARTS YOU NEED.

| | |
|---|------------|
| d | 28 mm |
| D | 52 mm |
| B | 12 mm |
| rs min | 0.6 mm |
| Radial clearance class | C3 |
| Mass | 0.1 kg |
| Dynamic load, C | 12.5 kN |
| Static load, C0 | 7.4 kN |
| Fatigue limit load, Cu | 0.34 kN |
| f0 | 14.5 |
| Nlim (oil) | 16,000 rpm |
| Nlim (grease) | 14,000 rpm |
| Min operating temperature, Tmin | -60 °C |
| Characteristic cage frequency, FTF | 0.41 Hz |
| Characteristic rolling element frequency, BSF | 5.42 Hz |
| Characteristic outer ring frequency, BPF0 | 4.11 Hz |
| Characteristic inner ring frequency, BPFI | 5.89 Hz |
| da min | 32 mm |
| Da max | 48 mm |
| ra max | 0.6 mm |

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4547359541687 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 28MM Bore; 52MM Outside Diameter; 12MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil |
| Other Features | Deep Groove Shell Alvania Prelubricated |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 0.205 |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Bore | 1.102 Inch 28 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outside Diameter | 2.047 Inch 52 Millimeter |