

ISO 7034 B angular contact ball bearings

Online shopping ISO 7034 B angular contact ball bearings from a great selection at 92.075 mm db Store. ... 80 mm da Accessories.

da	80 mm
db	92.075 mm
dc	76.2 mm
Da	140 mm
Ca	42.799 mm
A1	88.9 mm
A2	126.603 mm
S	4.763 mm
ba	34.131 mm
H	169.863 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N1	22.225 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	31.75 mm
Housing	SAF 216

Bearing	22216 E
Lock nut	AN 16
Lock washer	W 16
Stabilizing ring	SR-16-13
Labyrinth ring (db shaft position)	LOR 82
PosiTrac Plus contact element (db shaft position)	B10724-79
Labyrinth ring (dc shaft position)	LOR 54
PosiTrac Plus contact element (dc shaft position)	B10724-53
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1450 r/min
P60°	83.2 kN
P90°	49.8 kN
P120°	30.2 kN
P150°	26.7 kN
P180°	31.6 kN
Pa	20.5 kN
Mass pillow block	15.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	175.77 g