

# ISO 709 A angular contact ball bearings

LET OUR 0.0 Inventory ISO 709 A angular contact ball bearings EXPERTS GET YOU N/A Minimum Buy Quantity THE PARTS YOU NEED. ASAHI BEARINGS Manufacturer Name

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.66  |
| EAN                       | 0808250320967   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Adjustable Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Nickel Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | UC205-15  |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 2 Bolt Adjustable Flange Block; 15/16" Bore; 3.9" Bolt Circle; 3-55/64" Bolt Spacing; |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Single Row   Spherical   Normal Duty   Adjustable   Has Slinger |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.40   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Weight / LBS                       | 1.45  |
| Nominal Bolt Circle Diameter Round | 3.9 Inch   99 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter   |
| D                                  | 1.339 Inch   34 Millimeter                                      |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter   |
| d                                  | 0.938 Inch   23.825 Millimeter                                  |
| Bolt Spacing                       | 3.859 Inch   98.019 Millimeter                                  |