

ISO 71800 C angular contact ball bearings

The online ISO 71800 C angular contact ball bearings parts store 95.809 mm Ca gives you immediate access to a selection of more 309.999 mm Da than 1.4 million new, 182.563 mm da used, remanufactured.

da	182.563 mm
Da	309.999 mm
Ca	95.809 mm
A1	171.45 mm
A2	247.65 mm
ba	74.612 mm
H	358.775 mm
H1	179.4 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	49.212 mm
Housing	SAFS 040 KA
Bearing	23040 CCK/W33

Adapter sleeve assembly	SNW 3040×7.3/16
Stabilizing ring	2 x 38151-40
Labyrinth ring	2 x LOR 159
PosiTrac Plus contact element	2 x B10724-159
End plug (suffix Y)	EPR 21
Max. speed for PosiTrac Plus seal	800 r/min
P60°	345 kN
P90°	207 kN
P120°	127 kN
P150°	113 kN
P180°	133 kN
Pa	48.9 kN
Mass pillow block	156 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g