

ISO 71807 A angular contact ball bearings

ISO 71807 A angular contact ball bearings 85.725 mm da Industries and Applications ? We sell discount online as well as cheap machinery parts.

da	85.725 mm
Da	215.001 mm
Ca	82.804 mm
A1	120.65 mm
A2	187.325 mm
ba	45.244 mm
H	258.762 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	55.563 mm
Housing	SAF 620
Bearing	1320 K
Adapter sleeve assembly	SNW 120×3.3/8

Stabilizing ring	2 x SR-1620
Labyrinth ring	2 x LOR 101
End plug (suffix Y)	EPR 12
Bearing limiting speed	4000 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	14 kN
Mass pillow block	45.9 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	765.45 g