

ISO 71910 CDT angular contact ball bearings

Online shopping ISO 71910 CDT angular contact ball bearings from a great selection at Store. ... 130 mm da Accessories. 149.225 mm db

da	130 mm
db	149.225 mm
dc	125.412 mm
Da	279.999 mm
Ca	102.794 mm
A1	158.75 mm
A2	288.925 mm
S	4.763 mm
ba	72.231 mm
H	336.55 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	61.913 mm

Housing	SAF 326
Bearing	22326 CC/W33
Lock nut	AN 26
Lock washer	W 26
Stabilizing ring	SR-0-26
Taconite seal (db shaft position)	TER 136
Taconite seal (dc shaft position)	TER 122
End plug (suffix Y)	EPR 27
Max. speed for Taconite seal	520 r/min
P60°	226 kN
P90°	136 kN
P120°	85.9 kN
P150°	78.3 kN
P180°	94.3 kN
Pa	60.9 kN
Mass pillow block	100 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g