

ISO 7208 ADT angular contact ball bearings

Shop ISO 7208 ADT angular contact ball bearings huge online discount inventory. and Import machinery parts your car needs with Free 50 Bore Diameter (mm) Shipping and 50x72x12 Size (mm) Free Extended Warranty.

Size (mm)	50x72x12
Bore Diameter (mm)	50
Outer Diameter (mm)	72
Width (mm)	12
d	50 mm
D	72 mm
B	12 mm
C	12 mm
a	1.7 mm
b	0.95 mm
f	0.85 mm
r min.	0.6 mm
r1 min.	0.5 mm
D1	70.7 mm
D2	74.8 mm
Weight	0.127 Kg
Basic dynamic load rating (C)	14,5 kN
Basic static load rating (C0)	11,7 kN
(Grease) Lubrication Speed	9500 r/min
Enclosure	Single Shield with Snap Ring
Bore Type	Cylindrical Bore

Configuration	Single Row
Bore Size	50 mm
Outside Diameter	72 mm
Width	12 mm
Fillet Radius/Chamfer	0.6 mm
r1	0.5 mm
Snap Ring Width	0.9 mm
Snap Ring Outside Diameter	74.8 mm
D1 (max)	70.7 mm
a (max)	1.7 mm
b (min)	1 mm
Dynamic Load Rating	14,500 N
Static Load Rating	11,700 N
Limiting Speed – Grease	9,500 rpm
Limiting Speed – Oil	11,000 rpm
Factor fo	16.1
Radial Clearance	0.006 to 0.023 mm
da (min)	54 mm
Da (max)	68 mm
Dx (min)	76 mm
ra (max)	0.6 mm
Cy (max)	2.3 mm