

# ISO 7303 C angular contact ball bearings

With over 10170 full-service stores, our ISO 7303 C angular contact ball bearings inventory is extensive and our parts are 0.0 Inventory priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

|                           |                     |
|---------------------------|---------------------|
| Inventory                 | 0.0                 |
| Manufacturer Name         | REGAL BELOIT        |
| Minimum Buy Quantity      | N/A                 |
| Weight                    | 0.999               |
| EAN                       | 0662461058398       |
| Product Group             | M06110              |
| Number of Mounting Holes  | 2                   |
| Mounting Method           | Set Screw           |
| Housing Style             | 2 Bolt Flange Block |
| Rolling Element           | Ball Bearing        |
| Housing Material          | Cast Iron           |
| Expansion / Non-expansion | Non-expansion       |
| Mounting Bolts            | 15/32 Inch          |
| Relubricatable            | Yes                 |
| Insert Part Number        | 2-13-CTJ            |
| Seals                     | Felt Labyrinth      |
| Housing Configuration     | 1 Piece Solid       |
| Pilot Configuration       | No Pilot            |
| Inch – Metric             | Inch                |

|                                    |   |
|------------------------------------|---|
| Long Description                   | 2 Bolt Flange Block; 1-3/16" Bore; 4.6" Bolt Circle; 4-19/32" Bolt Spacing; 1 Piece S |
| Other Features                     | Single Row   Standard Duty   Has Flinger  |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.40   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Manufacturer Item Number           | SFT-19 CTJ  |
| Manufacturer Internal Number       | 711466  |
| Weight / LBS                       | 2.2   |
| d                                  | 1.188 Inch   30.175 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter   |
| Bolt Spacing                       | 4.594 Inch   116.7 Millimeter   |
| D                                  | 1.5 Inch   38.1 Millimeter  |
| Nominal Bolt Circle Diameter Round | 4.6 Inch   117 Millimeter   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter   |