

ISO 7309 B angular contact ball bearings

Can't find what you're looking for Mounted Bearing Engineering Group ISO 7309 B angular contact ball bearings ? Our expert Representatives 2-15/16 in Shaft Size be in contact with you shortly!

| | |
|-------------------------|------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 2-15/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | TAPG17K215SB |
| Locking Style | Tapered Adapter |
| Weight | 37.0 lb |
| Housing Style | Four-Bolt Pillow Block |
| UPC Code | 0883450127370 |
| Dimension A | 3.74 in |
| Dimension B | 7.20 in |
| Dimension C | 4.33 in |
| Dimension D Max | 11.31 in |
| Dimension D Min | 9.44 in |
| Dimension E | 2.06 in |
| Dimension F | 12.63 in |
| Dimension G | 3.630 in |
| Dimension H | 1.25 in |
| Dimension J (Bolt Size) | 0.750 in |
| Dimension L | 3.78 in |
| Dimension M | 1.96 in |
| Dimension S | 3.23 in |

| | |
|---------------------------------------|-----------|
| C0 – Static Load | 71900 lb |
| C – Dynamic Load (Basic) | 66900 lb |
| e – Geometry Factor | 0.22 |
| Y1 – Geometry Factor | 3.07 |
| Y2 – Geometry Factor | 4.57 |
| Oil Lubrication – M/N Seal | 1400 rpm |
| Oil Lubrication – T Seal | 2400 rpm |
| Oil Lubrication – B/C/O Seal | 1100 rpm |
| Grease Lubrication – M/N Seal | 1400 rpm |
| Grease Lubrication – T Seal | 2000 rpm |
| Grease Lubrication – B/C/O Seal | 1100 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0040 in |
| Pre Install Clearance Min | 0.0043 in |
| Pre Install Clearance Max | 0.0055 in |
| Int Radial Clearance Reduction Min | 0.0018 in |
| Int Radial Clearance Reduction Max | 0.0025 in |
| Adapter Sleeve Axial Movement Min | 0.027 in |
| Adapter Sleeve Axial Movement Max | 0.038 in |
| Post Install Int Radial Clearance Min | 0.0020 in |