

ISO 7320 CDT angular contact ball bearings

170 Million used ISO 7320 CDT angular contact ball bearings instantly searchable. Shop our large selection of 68x40x15 Size (mm) parts based on brand, price, description, and location. Order the with stock ...

Size (mm)	68x40x15
Bore Diameter (mm)	68
Outer Diameter (mm)	40
Width (mm)	15
d	40 mm
D	68 mm
B	15 mm
d1	49.2 mm
d2	49.2 mm
D1	58.8 mm
r1,2 – min.	1 mm
r3,4 – min.	0.3 mm
a	14.8 mm
da – min.	44.6 mm
db – min.	44.6 mm
Da – max.	63.4 mm
Db – max.	66 mm
ra – max.	1 mm
rb – max.	0.3 mm
dn	50.8 mm
Basic dynamic load rating – C	16.8 kN

Basic static load rating – C0	11 kN
Fatigue load limit – Pu	0.465 kN
Limiting speed for grease lubrication	24000 r/min
Limiting speed for oil lubrication	38000 mm/min
Ball – Dw	7.938 mm
Ball – z	18
Gref	2.4 cm ³
Calculation factor – f0	10
Preload class A – GA	60 N
Preload class B – GB	120 N
Preload class C – GC	240 N
Preload class D – GD	480 N
Calculation factor – f	1
Calculation factor – f2A	1
Calculation factor – f2B	1.02
Calculation factor – f2C	1.05
Calculation factor – f2D	1.09
Calculation factor – fHC	1.02
Preload class A	42 N/micron
Preload class B	56 N/micron
Preload class C	76 N/micron
Preload class D	107 N/micron
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.183
Product Group	B04270
Enclosure	Open

Precision Class	ABEC 7 ISO P4
Material – Ball	Ceramic
Number of Bearings	1 (Single)
Contact Angle	15 Degree
Preload	None
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row Angular Contact High Precision Hybrid Corrosion Resistant Ball
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Ceramic Bal
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer Item Number	7008 CD/HCP4A
Weight / LBS	0.399
Bore	1.575 Inch 40 Millimeter
Width	0.591 Inch 15 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter

r _{1,2} min.	1 mm
r _{3,4} min.	0.3 mm
d _a min.	44.6 mm
d _b min.	44.6 mm
D _a max.	63.4 mm
D _b max.	66 mm
r _a max.	1 mm
r _b max.	0.3 mm
Basic dynamic load rating C	16.8 kN
Basic static load rating C ₀	11 kN
Fatigue load limit P _u	0.465 kN
Attainable speed for grease lubrication	24000 r/min
Attainable speed for oil-air lubrication	38000 r/min
Ball diameter D _w	7.938 mm
Number of balls z	18
Reference grease quantity G _{ref}	2.4 cm ³
Preload class A GA	60 N
Static axial stiffness, preload class A	42 N/μm
Preload class B GB	120 N
Static axial stiffness, preload class B	56 N/μm
Preload class C GC	240 N
Static axial stiffness, preload class C	76 N/μm
Preload class D GD	480 N
Static axial stiffness, preload class D	107 N/μm

Calculation factor f	1.06
Calculation factor f1	1
Calculation factor f2A	1
Calculation factor f2B	1.02
Calculation factor f2C	1.05
Calculation factor f2D	1.09
Calculation factor fHC	1.02
Calculation factor f0	10
Mass bearing	0.17 kg