

# ISO 89308 thrust roller bearings

Find the discount ISO 89308 thrust roller bearings online you need . We REGAL BELOIT Manufacturer Name offer 0.0 Inventory ... If you check out our large selection of ISO 89308 thrust roller bearings once .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 2.36   |
| EAN                       | 0662798361307  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | B250R  |
| Seals                     | Nitrile Rubber   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Spherical   High Base   Anti Rotation Pin   Has Trash Guard |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-3/4" Bore; 2-1/8" Base to Center Height; Set Screw Mount; Ball Bear |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | 1001-07090   |
| Manufacturer Internal Number  | 36130  |
| Weight / LBS                  | 5.2  |
| d                             | 1.75 Inch   44.45 Millimeter   |
| B                             | 2.125 Inch   53.98 Millimeter  |
| Bolt Spacing Maximum          | 5.969 Inch   151.6Millimeter   |
| Nominal Bolt Center to Center | 5.8 Inch   146.5 Millimeter  |
| D                             | 1.622 Inch   41.2 Millimeter   |
| Bolt Spacing Minimum          | 5.5 Inch   139.7Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |