

# ISO 89310 thrust roller bearings

High Quality ISO 89310 thrust roller bearings. Competitive Pricing. Accept 23 mm B Small 45 mm d Order. Easy and Fast 85 mm D Shipping.

d	45 mm
D	85 mm
B	23 mm
E	76.5 mm
F	54.5 mm
rs min	1.1 mm
r1s min	1.1 mm
Radial clearance class	C3
Mass (without HJ ring)	0.52 kg
Dynamic load, C	76 kN
Static load, C0	84.5 kN
Fatigue limit load, Cu	10.3 kN
Nlim (oil)	8,000 rpm
Nlim (grease)	6,800 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.79 Hz
Characteristic outer ring frequency, BPF0	6.24 Hz
Characteristic inner ring frequency, BRFI	8.76 Hz
da min	51.5 mm
da max	54 mm

db min	57 mm
Da max	78.5 mm
ra max	1 mm
r1a max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.519
EAN	4547359140910
Product Group	B04144