

# ISO BK304016 cylindrical roller bearings

Online shopping ISO BK304016 cylindrical roller bearings from a 110 Outer Diameter (mm) great 160x110x70 Size (mm) selection at 160 Bore Diameter (mm) Store. ... Accessories.

Size (mm)	160x110x70
Bore Diameter (mm)	160
Outer Diameter (mm)	110
Width (mm)	70
d	110 mm
D	160 mm
B	70 mm
C	55 mm
$\alpha$	6 °
dk	140 mm
r1 – min.	1 mm
r2 – min.	1 mm
da – min.	118 mm
da – max.	121 mm
Da – min.	141.5 mm
Da – max.	153 mm
ra – max.	1 mm
rb – max.	1 mm
Basic dynamic load rating – C	1860 kN
Basic static load rating – C0	3100 kN
Specific factor dinamic load – K	300 N/mm <sup>2</sup>

Specific factor static load – K0	500 N/mm2
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	4.545
EAN	7316572041987
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material – Outer Member	Stainless Steel
Material – Ball	Stainless Steel
Material – Liner	Teflon
Relubricatable	No
Enclosure	2 Seals
Other Features	2 Piece   Corrosion Resistance   Axially Split Outer Ring   Self Lubricating   Triple Lip Heavy Duty
Long Description	110MM Bore; 55MM Housing Width; 160MM Outside Diameter; Spherical Plain; Stainless Steel Outer Membe
Inch – Metric	Metric
UNSPSC	31171515
Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial
Manufacturer Item Number	GE 110 TXG3A-2LS

Weight / LBS	10.582
Housing Width	2.165 Inch   55 Millimeter
Overall Width	2.756 Inch   70 Millimeter
Bore	4.331 Inch   110 Millimeter
Outside Diameter	6.299 Inch   160 Millimeter
Lubricant	Maintenance free – dry lubrication
Design (sliding contact surface combination)	Steel/PTFE fabric
Sealing solution	Triple-lip seals
$\alpha$	6 °
r1 min.	1 mm
r2 min.	1 mm
da min.	118 mm
da max.	121 mm
Da min.	141.5 mm
Da max.	153 mm
ra max.	1 mm
rb max.	1 mm
Basic dynamic load rating C	1860 kN
Basic static load rating C0	3100 kN
Specific dynamic load factor K	300 N/mm <sup>2</sup>
Specific static load factor K0	500 N/mm <sup>2</sup>
Mass plain bearing	4.8 kg