

# ISO BK5020 cylindrical roller bearings

LET OUR ISO BK5020 cylindrical roller bearings EXPERTS GET YOU 1.1875 in d 1-37/64 in horizontal bolt spacing: THE PARTS YOU NEED.

|                               |                          |
|-------------------------------|--------------------------|
| d                             | 1.1875 in                |
| horizontal bolt spacing:      | 1-37/64 in               |
| bore type:                    | Round                    |
| vertical bolt spacing:        | 1-9/64 in                |
| duty type:                    | Standard Duty            |
| shaft centerline height:      | 1-31/32 in               |
| mounting type:                | Three-Bolt Bracket Style |
| hub diameter:                 | 3-5/64 in                |
| housing material:             | Cast Iron                |
| bracket width:                | 2-9/16 in                |
| locking device:               | Set Screw                |
| unit standoff:                | 1-37/64 in               |
| radial dynamic load capacity: | 4410 lbf                 |
| bolt size:                    | 3/8                      |
| radial static load capacity:  | 2540 lbf                 |
| lubrication type:             | Lubrication Fitting      |
| seal type:                    | Contact with Flinger     |
| series:                       | UCFK200C4HR23            |
| length through bore:          | 1.500 in                 |
| replacement bearing:          | UC206-19C4HR23           |