

ISO DAC38720034 angular contact ball bearings

How do I place an 180 mm Da EMERGENCY order for a ISO DAC38720034 angular contact ball bearings that 106.362 mm da I want to pick up at 55.804 mm Ca a our store?

da	106.362 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
ba	46.831 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	39.688 mm
Housing	FSAF 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024×4.3/16

Stabilizing ring	2 x 38151-24
Labyrinth ring	2 x LOR 113
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1350 r/min
P60°	119 kN
P90°	71.2 kN
P120°	44.5 kN
P150°	40 kN
P180°	48.9 kN
Pa	16.7 kN
Mass pillow block	28.6 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g