

# ISO GE 120 XES plain bearings

170 Million used ISO GE 120 XES plain bearings instantly 0.0 Inventory searchable. Shop our large selection of parts based on brand, price, description, and location. TIMKEN Manufacturer Name Order the with stock ...

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.718   |
| EAN                       | 0883450191838   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22213   |
| Seals                     | Triple Lip Nitrile Rubber   |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>65MM Bore; 171.5MM Bolt Circle;<br>121.158MM Bolt Spacing; 1 Piece<br>Solid; C |

|                                       |  |
|---------------------------------------|--|
| Other Features                        | Double Row   Double Collar  <br>With Set Screw |
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | QAAFL13A065SEM                                 |
| Weight / LBS                          | 17   |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                          |
| Nominal Bolt Circle Diameter<br>Round | 6.8 Inch   171.5 Millimeter                    |
| D                                     | 4.3 Inch   109.22 Millimeter                   |
| d                                     | 2.559 Inch   65 Millimeter                     |
| Bolt Spacing                          | 4.77 Inch   121.158 Millimeter                 |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                          |