

ISO GE 180 ES plain bearings

LET OUR ISO GE 180 ES plain bearings 17x40x12 Size (mm)
EXPERTS GET YOU 17 Bore Diameter (mm) 40 Outer Diameter (mm)
THE PARTS YOU NEED.

Size (mm)	17x40x12
Bore Diameter (mm)	17
Outer Diameter (mm)	40
Width (mm)	12
d	17 mm
D	40 mm
B	12 mm
C	12 mm
r min.	0,6 mm
da min.	21 mm
da max	23 mm
Da max.	36 mm
ra max.	0,6 mm
Weight	0,066 Kg
Basic dynamic load rating (C)	9,6 kN
Basic static load rating (C0)	4,6 kN
Reference speed	15 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.066
EAN	4547359559286
Product Group	B00308

Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Low Torque Nitrile Friction Seal -25 To 250 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6203LLH
Weight / LBS	0.146
Outside Diameter	1.575 Inch 40 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	0.669 Inch 17 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
bore diameter:	17 mm
precision rating:	ISO Class 0
outside diameter:	40 mm
finish/coating:	Uncoated

overall width:	12 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	12 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	12 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	15000 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	21000 RPM
dynamic load capacity:	9600 N
series:	62
static load capacity:	4600 N
manufacturer product page:	Click here