

# ISO GE15F0-2RS plain bearings

Offer High Quality Brand 130 D ISO GE15F0-2RS plain bearings 60 d .Contact 9 Days or more Days to Ship Us Online to Get Best Quote.

|                                      |  |
|--------------------------------------|--|
| Days to Ship                         | 9 Days or more                                     |
| d                                    | 60   |
| D                                    | 130  |
| B                                    | 31   |
| Precision (JIS)                      | Grade 0  |
| Number of Raceway Ring Rows          | Single Row   |
| Specifications/Environment           | Standard   |
| Basic Load Rating, Dynamic Rating(N) | 124000   |
| Internal Clearance Symbol            | CM   |
| Shaft Bore Config.                   | Cylindrical Bore                                   |
| Format symbol                        | NU (double brims for the outer ring)               |
| Holder Symbol                        | G1 (high tensile brass square hole holder without) |
| Specifications                       | Standard   |
| Symbol of Bearing Ring Shape         | No symbol: Internal diameter cylinder hole         |
| Revolution Frequency(rpm)            | 5500   |
| Outer ring oil hole                  | M (with fitting nozzle for oil mist)               |
| Large-capacity type                  | Standard   |
| Combination of two pieces            | Standard   |
| Cylinder shape (suffix symbol: X)    | No   |

|                           |                    |
|---------------------------|--------------------|
| Raceway Ring Shape        | Cylindrical Roller |
| Load Direction            | Radial             |
| Inner/Outer Ring Material | Steel              |
| Rolling Element Material  | Steel              |
| High-Speed Steel          | Standard           |