

ISO GE260FW-2RS plain bearings

Online ISO GE260FW-2RS plain bearings Expert. More Choices. ISO GE260FW-2RS plain bearings 15 mm d in Stock & Ready to Ship Now!

d	15 mm
D	35 mm
B	11 mm
rs min	0.6 mm
Radial clearance class	C2
Mass	0.04 kg
Dynamic load, C	7.75 kN
Static load, C ₀	3.6 kN
Fatigue limit load, C _u	0.16 kN
f ₀	12.7
N _{lim} (grease)	19,000 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.68 Hz
Characteristic outer ring frequency, BPF ₀	2.61 Hz
Characteristic inner ring frequency, BRF ₀	4.39 Hz
da min	19 mm
da max	20 mm

Da max	31 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.045
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C2-Snug
Inch – Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.099

Outside Diameter	1.378 Inch 35 Millimeter
Outer Race Width	0.433 Inch 11 Millimeter
Bore	0.591 Inch 15 Millimeter
Inner Race Width	0 Inch 0 Millimeter