

ISO GE80XD0 plain bearings

How do 76.2×168.275×53.975 Size (mm) I 76,2 Bore Diameter (mm) place an EMERGENCY order for a ISO GE80XD0 plain bearings that I want to 168,275 Outer Diameter (mm) pick up at a our store?

Size (mm)	76.2×168.275×53.975
Bore Diameter (mm)	76,2
Outer Diameter (mm)	168,275
Width (mm)	53,975
d	76,2 mm
D	168,275 mm
T	53,975 mm
B	56,363 mm
C	41,275 mm
ra1 max.	3,3 mm
a	35,2 mm
r min.	0,8 mm
r1 min.	3,3 mm
Da	149 mm
db	89 mm
ra max.	0,8 mm
da	90 mm
Db	155 mm
Weight	5,87 Kg
Basic dynamic load rating (C)	345 kN
Basic static load rating (C0)	470 kN
(Grease) Lubrication Speed	2200 r/min
(Oil) Lubrication Speed	3000 r/min

Calculation factor (e)	0,3
Calculation factor (Y0)	1,1
LangID	1
ALP23	0
outer r	3.3
ALP22	34
D_	168.275
ALP21	22
SHOG_yobi	837R/832R
RAr	394.3
inner r	0.8
GRS rpm	2200
D_b	155
D_a	149
DE_	146.294
SLR	41
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	11.283
SDM_	125.963
DA1	21.789
DA2	19.531
hidYobi	837/832
Y1	2
B_	56.363
Oil rpm	3000
hidTable	ecat_NSTPRI
Y0	1.1
inner ra	0.8

outer rb	3.3
C0	470
CUP	1.74
e	0.3
DA_	20.665
BET21	3
BET22	10
BET23	0
Z_	16
C_	41.275
yobi	837/832
KBRG	3161
CONE	4.13
DI_	105.51