

ISO HH932145/10 tapered roller bearings

Shop 65x140x60.2 Size (mm) ISO HH932145/10 tapered roller bearings huge online discount inventory. 140 Outer Diameter (mm) and Import machinery parts your car needs with Free Shipping and Free Extended Warranty.

Size (mm)	65x140x60.2
Bore Diameter (mm)	65
Outer Diameter (mm)	140
Width (mm)	60,2
d	65 mm
D	140 mm
T	60,2 mm
d1	140 mm
r min.	2 mm
A	40 mm
D1	68 mm
R	112 mm
da min.	110 mm
Da max.	95 mm
ra max.	2 mm
Weight	4,22 Kg
Basic dynamic load rating (C)	234 kN
Basic static load rating (C0)	495 kN
(Grease) Lubrication Speed	1100 r/min
Inventory	0.0
Manufacturer Name	NSK

Minimum Buy Quantity	N/A
Weight / Kilogram	5.28
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Aligning Seat
Long Description	65MM Bore 1; 68MM Bore 2; 140MM Outside Diameter; 60.2MM Height; Ball Bearing; Single Direction; Not
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Weight / LBS	9.30351
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
Bore 1	2.559 Inch 65 Millimeter
Height	2.37 Inch 60.2 Millimeter
Bore 2	2.677 Inch 68 Millimeter
SRI	14.5
hidYobi	53413

LangID	1
D_	140
SREX	0.1
C	234
B_	60.2
hidTable	ecat_NSSDTB
Oil rpm	1700
SRE	14.5
mass	4.22
GRS rpm	1100
ra	2
SRIX	0.1
D_a	95
SRIN	0
C0	495
SREN	0
D_1	68
Prod_Type3	TB_SD_WAS
da	110
DA_	26.988
Z_	11
yobi	53413
A_	40
T3	60.2
SDM_	102.5
r	2
KBRG	5121
R_	112