

ISO HK091514 cylindrical roller bearings

We work closely with our ISO HK091514 cylindrical roller bearings manufacturing partners to bring 0.0 Inventory the best value to customers.

| | |
|----------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.17 |
| EAN | 7316577087324 |
| Product Group | B04270 |
| Enclosure | Open |
| Precision Class | ABEC 7 ISO P4 |
| Material – Ball | Steel |
| Number of Bearings | 2 (1 Pair) |
| Contact Angle | 15 Degree |
| Preload | Medium |
| Raceway Style | 1 Rib Outer Ring |
| Cage Material | Phenolic |
| Rolling Element | Ball Bearing |
| Mounting Arrangement | Duplex-Universal |
| Flush Ground | Yes |
| Inch – Metric | Metric |
| Other Features | Single Row Angular Contact High Precision |

| | |
|-------------------------------|---|
| Long Description | 35MM Bore; 55MM Outside Diameter; 20MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact Ball |
| Manufacturer Item Number | 71907 CD/P4ADGB |
| Weight / LBS | 0.379 |
| d | 1.378 Inch 35 Millimeter |
| B | 0.787 Inch 20 Millimeter |
| D | 2.165 Inch 55 Millimeter |
| bore diameter: | 35 mm |
| radial dynamic load capacity: | 9.75 kN |
| outside diameter: | 55 mm |
| radial static load capacity: | 6.55 kN |
| overall width: | 10 mm |
| bearing material: | Steel |
| contact angle: | 15 ° |
| maximum rpm: | 40000 RPM |
| internal clearance: | C0 |
| finish/coating: | Uncoated |
| ball screw application: | Not for Ball Screws |
| outer ring width: | 10 mm |
| closure type: | Open |
| fillet radius: | 0.6 mm |
| precision rating: | ABEC 7 (ISO Class 4) |
| series: | 71 |