

ISO HK1716 cylindrical roller bearings

We Provide Extensive ISO HK1716 cylindrical roller bearings 47 Outer Diameter (mm) Selection And Competitive 17x47x19 Size (mm) Wholesale Pricing.

| | |
|-------------------------------|--------------|
| Size (mm) | 17x47x19 |
| Bore Diameter (mm) | 17 |
| Outer Diameter (mm) | 47 |
| Width (mm) | 19 |
| d | 17 mm |
| D | 47 mm |
| B | 19 mm |
| C | 19 mm |
| r min. | 1 mm |
| da min. | 22 mm |
| Da max. | 42 mm |
| ra max. | 1 mm |
| Weight | 0,15 Kg |
| Basic dynamic load rating (C) | 14,7 kN |
| Basic static load rating (C0) | 3,55 kN |
| (Grease) Lubrication Speed | 13 000 r/min |
| (Oil) Lubrication Speed | 16 000 r/min |
| Calculation factor (e) | 0,51 |
| Calculation factor (Y0) | 1,3 |
| Calculation factor (Y1) | 1,2 |
| rs min | 1 mm |
| e | 0.51 |

| | |
|---------------------------------|------------|
| Y1 | 1.2 |
| Y2 | 1.9 |
| Y0 | 1.3 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.15 kg |
| Dynamic load, C | 14.7 kN |
| Static load, C0 | 3.55 kN |
| Nlim (oil) | 16,000 rpm |
| Nlim (grease) | 13,000 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| da min | 22 mm |
| Da max | 42 mm |
| ra max | 1 mm |