

ISO HM125948/10 tapered roller bearings

ISO HM125948/10 tapered roller bearings TIMKEN Manufacturer Name with easy-to-use parts graphics, giving you the ability to check parts availability, 0.0 Inventory pricing, examine remanufactured options.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	106 lb
EAN	0013992041722
Product Group	B04144
Number of Mounting Holes	2
Mounting Method	Clamp Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	MSE315BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row Medium Duty With Support Wide Inner Ring
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	92.58
D	3.626 Inch 92.1 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Actual Bolt Center to Center	15.4 Inch 392Millimeter
B	5.63 Inch 143 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Nominal Bolt Center to Center	15.4 Inch 392 Millimeter
d	3.938 Inch 100.025 Millimeter
Shaft Size	3-15/16 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Two-Bolt Plummer Block
Series Type	Medium Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Standard
Bolt Size	2 x M24
Dimension H	5.630 in
Dimension H1	2.4 in
Dimension H2	12.4 in
Dimension J	15.4 in
Dimension L	18.3 in
Dimension M	4.7 in
Housing Width	5.7 in
Cr – Dynamic Load Rating	87226 lbf
Cor – Static Load Rating	110381 lbf
Ca – Axial Load Rating	5620 lbf

Maximum Speed	2130 rpm
Note	This product line was formerly known as "Revolvo"