

ISO HM212046/11 tapered roller bearings

170 Million used ISO HM212046/11 tapered roller bearings instantly searchable. Shop our large selection of parts TIMKEN Manufacturer Name based on 0.0 Inventory brand, price, description, and location. Order the with stock ...

| | |
|--------------------------|---------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| EAN | 0883450507578 |
| Weight / US pound | 0.01 |
| Product Group | M06110 |
| Shaft Size | 3.4375 in |
| Shaft Size Type | Imperial |
| Weight | 45 lb |
| UPC Code | 0883450507578 |
| Type E Open Cover Number | EUDR-3 3/16 |
| Dimension B | 5 in |
| Dimension L | 13-1/2 in |
| Dimension A | 4-1/2 in |
| Dimension J Min. | 10-3/4 in |
| Dimension J Max. | 11-1/4 in |
| Bolt Diameter | 3/4 in |
| Dimension N | 15/16 in |
| Dimension N1 | 1-3/16 in |
| Dimension N2 | 2-3/8 in |
| Dimension H1 | 2-1/4 in |

| | |
|--|---|
| Dimension H2 | 7-1/2 in |
| Dimension d1 | 5-17/32 in |
| Dimension H | 3-3/4 in |
| Dimension Ac | 5.8 in |
| Dimension d2 | 6.7 in |
| e | 0.50 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 1.71 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 2.07 |
| K Factor | 1.19 |
| C90 Dynamic Load Rating ¹ | 19600 lb |
| C0 Static Load Rating | 108600 lb |
| Fa-max Maximum Permissible Thrust Load ² | 5181 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ³ | 16000 lb |
| Max. Speed ⁴ | 1640 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |