

ISO HM252349/10 tapered roller bearings

How do 170 Bore Diameter (mm) you find the ISO HM252349/10 tapered roller bearings specification? Manufacturers Online Free check 170x280x74 Size (mm)

| | |
|---------------------|-------------------------------------|
| Size (mm) | 170x280x74 |
| Bore Diameter (mm) | 170 |
| Outer Diameter (mm) | 280 |
| Width (mm) | 74 |
| d1H | 170 mm |
| D | 280 mm |
| B | 74 mm |
| a | 6 mm |
| b | 17 mm |
| D1 | 254,3 mm |
| Da max | 269,8 mm |
| d | 180 mm |
| d2 | 201,8 mm |
| d2G | M190X3 |
| da min | 190,2 mm |
| ds | 8 mm |
| l | 92 mm |
| ns | 15 mm |
| ra max | 2,1 mm |
| rmin | 2,1 mm |
| m | 15,6 kg / Weight |
| m1 | 2,87 kg / Weight, withdrawal sleeve |

| | |
|-----|---|
| Cr | 1040000 N |
| e | 0,23 |
| Y1 | 2,9 |
| Y2 | 4,31 |
| C0r | 1450000 N / Static load rating (radial) |
| Y0 | 2,83 |
| nG | 2600 1/min / Limiting speed |
| nB | 1790 1/min / Reference speed |