

# ISO JM738249A/10 tapered roller bearings

Enjoy High Margins on 0.0 Inventory Competitive Pricing.Great Wholesale Products at SKF Manufacturer Name N/A Minimum Buy Quantity Low Costs.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.12
EAN	7316577345554
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	YAR 213-211-2F
Seals	Single Lip Contact
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Flinger Seal
Long Description	2 Bolt Pillow Block; 2-11/16" Bore; 3" Base to Center Height; Set Screw Mount; Ball Bearin

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	13.4505
Bolt Spacing Minimum	7.563 Inch   192.1Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
Bolt Spacing Maximum	8.437 Inch   214.3Millimeter
D	2.689 Inch   68.301 Millimeter
d	2.688 Inch   68.275 Millimeter
Nominal Bolt Center to Center	8 Inch   203.2 Millimeter
B	3 Inch   76.2 Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	2.6875 in
overall width:	2-11/16 in
bore type:	Round
radial dynamic load capacity:	12870 lbf
base to bore centerline:	3.0000 in
radial static load capacity:	9000 lbf
duty type:	Normal Duty
base width:	65 mm
housing material:	Cast Iron
bolt center-to-center length:	203 mm
locking device:	Set Screw
maximum rpm:	3000 RPM
seal type:	Contact/Lip
lubrication type:	Lubrication Fitting
expansion type:	Non-Expansion Bearing (Fixed)

series:	SY
overall length:	257 mm
replacement bearing:	YAR 213-211-2F
overall height:	149 mm
standards met:	ISO