

ISO L68149/11 tapered roller bearings

ISO L68149/11 tapered roller bearings with easy-to-use parts graphics, giving you the ability to check parts Quote Days to Ship availability, pricing, examine remanufactured options.

| | |
|--|---|
| Days to Ship | Quote |
| RoHS | 6 |
| Type | Angular Contact Ball Bearing (Single Row) |
| Inner/Outer Ring Material | [Steel] Steel |
| Bearing Style | Open Type |
| Precision | Grade 5 |
| I.D.(Ø) | 80 |
| O.D.(Ø) | 170 |
| Width(mm) | 39 |
| Basic Dynamic Load Rating(N) | 147000 |
| Max. Allowed rpm(rpm) | 3600 |
| Specifications, Environment | Standard |
| Rolling Element Material | [Steel] Steel |
| Combination of Angular Contact Ball Bearings | Single Row |
| Retainer Type | Punching |
| Basic Load Rating, Static Rating(N) | 119000 |
| Clearance sign | CN (standard) |
| Preload | Normal preload |
| Contact angle(Degree) | 30 |
| Holder Symbol | No |

| | |
|------------------------------|-----------------|
| Symbol of Bearing Ring Shape | No |
| Seal, Shield Symbols | No |
| Precision Grade Symbol | P5 |
| Symbol of contact angle | A |
| Combination symbol | No |
| Preload Mark | No |
| Special Configurations Code | No |
| Bearing type symbol | No |
| Type symbol | No |
| Outer Ring Shape | Flat |
| Load Direction | Radial |
| Outer Ring | With Outer Ring |
| Size Standards | Metric System |