

# ISO LL584449/10 tapered roller bearings

ISO LL584449/10 tapered roller bearings 0.0 Inventory Product Brochures , Manufacturing Service . Get Your Free.

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	3.51
EAN	0692314630761
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Outer Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	2 Rib Inner Ring   Plain Outer Ring   Cage on Inner Ring OD

Long Description	100MM Bore; Straight Bore Profile; 180MM Outside Diameter; 34MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	N220G1C3
Weight / LBS	7.735
d	3.937 Inch   100 Millimeter
B	1.339 Inch   34 Millimeter
D	7.087 Inch   180 Millimeter
bore diameter:	100 mm
static load capacity:	217000 N
outside diameter:	180 mm
precision rating:	ISO Class 0
overall width:	34 mm
maximum rpm:	4500 rpm
flanges:	(2) Inner Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength Machined Brass Rivetless w/ square holes
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Outer Ring
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 °C

manufacturer product page:	<a href="#">Click here</a>
dynamic load capacity:	183000 N