

ISO LL788349/10 tapered roller bearings

With over 10170 full-service stores, our 6 Days Days to Ship ISO LL788349/10 tapered roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving Flat Outer Ring Shape time and your hard-earned 6 RoHS dollars.

Days to Ship	6 Days
RoHS	6
Outer Ring Shape	Flat
d	12
D	24
B	6
Basic Dynamic Load Rating(N)	2886
Revolution Frequency (Grease)(rpm)	31000
Basic Load Rating, Static Rating(N)	1466
Sealing Structure	Double Shielded
Type	Ball
Inner/Outer Ring Material	Steel
Precision	Grade 0
Specifications/Environment	Standard
Load Direction	Radial
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Rolling Element Material	Steel
Retainer Type	Punching
Bearing Style	Double Shielded

I.D.(Ø)	12
O.D.(Ø)	24
Width(mm)	6
Max. Allowed rpm(rpm)	30000
Clearance sign	CN (standard)
Accuracy(Class)	Class 0
Acoustic Symbol	No
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	ZZ
Precision Grade Symbol	No
Special Configurations Code	No
Rubugado Symbol	No
Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Specifications, Environment	Standard
Outer Ring	With Outer Ring
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No
Torque Symbol	No