

ISO LM567949/10 tapered roller bearings

ISO LM567949/10 tapered roller bearings with easy-to-use parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured 35x80x21 Size (mm) options.

Size (mm)	35x80x21
Bore Diameter (mm)	35
Outer Diameter (mm)	80
Width (mm)	21
d	35 mm
D	80 mm
B	21 mm
C	21 mm
r1 min.	1.5 mm
da min.	43 mm
Da max.	72 mm
ra max.	1.5 mm
Weight	0.510 Kg
Basic dynamic load rating (C)	25,1 kN
Basic static load rating (C0)	7,85 kN
(Grease) Lubrication Speed	7900 r/min
(Oil) Lubrication Speed	9700 r/min
Calculation factor (e)	0.25
Calculation factor (Y0)	2.60
Calculation factor (Y1)	2.48
Inventory	0.0
Manufacturer Name	NACHI

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-307X
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 3 Deg 1:12 Taper
Long Description	35MM Bore; Tapered Adapter Mount; 80MM Outside Diameter; 21MM Inner Race Width; 21MM Outer Race Width
Inch – Metric	Metric
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Weight / LBS	1.12436
Bore	1.378 Inch 35 Millimeter
Outer Race Width	0.827 Inch 21 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Inner Race Width	0.827 Inch 21 Millimeter