

ISO LM921845/10 tapered roller bearings

The online ISO LM921845/10 tapered roller bearings parts 58 Outer Diameter (mm) store gives you immediate access to 32x58x13 Size (mm) a selection of more than 1.4 million new, used, remanufactured.

Size (mm)	32x58x13
Bore Diameter (mm)	32
Outer Diameter (mm)	58
Width (mm)	13
d	32 mm
D	58 mm
B	13 mm
C	13 mm
r min.	1 mm
da min.	37 mm
da max	38,5 mm
Da max.	53 mm
ra max.	1 mm
Weight	0,122 Kg
Basic dynamic load rating (C)	15,1 kN
Basic static load rating (C0)	9,15 kN
(Grease) Lubrication Speed	12 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.121

EAN	0029176062636
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	32MM Bore; 58MM Outside Diameter; 13MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.269
Outer Race Width	0.512 Inch 13 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.283 Inch 58 Millimeter
Bore	1.26 Inch 32 Millimeter
SRI	4.01
hidYobi	60/32ZZ
LangID	1
D_	58
SREX	0.04

B_	13
da min	37
hidTable	ecat_NSRDGB
SRE	4.21
mass	0.122
GRS rpm	12000
ra	1
SRIX	0.02
D_a	53
SRIN	0
C0	9.15
fo	14.5
SREN	0
DE_	52.938
Prod_Type3	DGBB_SR_ZZ
DA_	7.938
bomp	0
Z_	10
yobi	60/32ZZ
C_conv	15100
ALPHA_	0
SDM_	45
r	1
KBRG	6141
SBRG	10
DI_	37.062