

# ISO NK20/16 needle roller bearings

Advance ISO NK20/16 needle roller bearings is your source for 0.0 Inventory quality and accessories. shop online for home delivery or pick up in one of our 10000 .

|  |               |
|--|---------------|
| Inventory                                | 0.0           |
| Manufacturer Name                        | TIMKEN        |
| Minimum Buy Quantity                     | N/A           |
| Weight                                   | 0             |
| EAN                                      | 0087796287181 |
| Product Group                            | M06288        |
| Design Unit                              | METRIC        |
| Bearing Weight                           | 0.9 Kg        |
| Cage Type                                | EM            |
| UPC Code                                 | 087796287181  |
| Cage Material                            | Brass         |
| Superseded Part                          | 22211YMC3     |
| d – Bore                                 | 55 mm         |
| D – Outer Diameter                       | 100 mm        |
| B – Inner Ring Width                     | 25 mm         |
| B – Outer Ring Width                     | 25 mm         |
| R – Inner Ring To Clear Radius1          | 1.5 mm        |
| r – Outer Ring To Clear Radius2          | 1.5 mm        |
| da – Inner Ring Backing Diameter         | 66.000 mm     |
| Da – Outer Ring Backing Diameter         | 91.000 mm     |
| C0 – Static Radial Rating                | 134000 N      |
| C1(2) – Dynamic Radial Rating (Two-Rows) | 134000 N      |

|   |       |
|---|-------|
| e – ISO Factor <sup>3</sup>                       | 0.23  |
| Y <sub>0</sub> – ISO Factor <sup>4</sup>          | 2.95  |
| Y <sub>1</sub> – ISO Factor <sup>5</sup>          | 4.4   |
| Y <sub>2</sub> – ISO Factor <sup>6</sup>          | 2.89  |
| Reference Thermal Speed Rating (Grease)           | 4700  |
| Reference Thermal Speed Rating (Oil) <sup>7</sup> | 5900  |
| C <sub>g</sub> – Geometry Factor <sup>8</sup>     | 0.052 |