

ISO NKXR 15 Z complex bearings

offers a ISO NKXR 15 Z complex bearings selection of Genuine at Wholesale Prices. N/A Minimum Buy Quantity We 0.0 Inventory are a ISO NKXR 15 Z complex bearings Certified Parts Retailer

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 1.535 |
| EAN | 7316577302816 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | Yes |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 80MM Bore; 140MM Outside Diameter; 26MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fi |
| Other Features | Deep Groove With Snap Ring |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |

| | |
|-----------------------------|----------------------------|
| Keyword String | Ball |
| Manufacturer Item Number | 6216 NR |
| Weight / LBS | 3.38 |
| Inner Race Width | 0 Inch 0 Millimeter |
| D | 140 mm |
| Outer Race Width | 1.024 Inch 26 Millimeter |
| d | 80 mm |
| B | 26 mm |
| d1 ≈ | 101.4 mm |
| D2 ≈ | 126.5 mm |
| D3 | 135.23 mm |
| D4 | 149.7 mm |
| b | 3.1 mm |
| C | 4.9 mm |
| f | 2.82 mm |
| r0 max. | 0.6 mm |
| r1,2 min. | 2 mm |
| da min. | 91 mm |
| Da max. | 129 mm |
| Db min. | 151 mm |
| ba min. | 3.5 mm |
| Ca max. | 7.72 mm |
| ra max. | 2 mm |
| Basic dynamic load rating C | 72.8 kN |
| Basic static load rating C0 | 55 kN |
| Fatigue load limit Pu | 2.2 kN |
| Reference speed | 9500 r/min |
| Limiting speed | 6000 r/min |
| Calculation factor kr | 0.025 |

| | |
|--------------------------|---------|
| Calculation factor f_0 | 15 |
| Mass bearing | 1.51 kg |
| Snap ring | SP 140 |