

ISO NN3006 K cylindrical roller bearings

Various types 70 mm Shaft Size and sizes to accommodate Mounted Bearing Engineering Group your ISO NN3006 K cylindrical roller bearings requirements.

| | |
|--------------------------|-------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 70 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QAAMC15A070SB |
| Locking Style | Double Concentric |
| Weight | 18.000 lb |
| Housing Style | Cartridge |
| UPC Code | 0883450303941 |
| Dimension A | 0.59 in |
| Dimension B | 1.03 in |
| Dimension C | 4.29 in |
| Dimension D | 0.25 in |
| Dimension F | 5.875 in |
| Dimension G | 3.140 in |
| Dimension L Exp | 4.04 in |
| Dimension L Fix | 3.96 in |
| Dimension M | 2.37 in |
| Dimension RAA | 0.78 in |
| Dimension SAA | 4.74 in |
| C0 – Static Load | 54100 lb |
| C – Dynamic Load (Basic) | 49900 lb |
| e – Geometry Factor | 0.22 |

| | |
|-------------------------------------|-----------|
| Y1 – Geometry Factor | 3.14 |
| Y2 – Geometry Factor | 4.67 |
| Oil Lubrication – M/N Seal | 1600 rpm |
| Oil Lubrication – T Seal | 2900 rpm |
| Oil Lubrication – B/C/O Seal | 1300 rpm |
| Grease Lubrication – M/N Seal | 1600 rpm |
| Grease Lubrication – T Seal | 2400 rpm |
| Grease Lubrication – B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance – Min | 0.0020 |
| Eng Internal Radial Clearance – Max | 0.0031 |
| Pre Install Clearance Min | 0.0020 in |
| Pre Install Clearance Max | 0.0031 in |