

# ISO NNU6026 cylindrical roller bearings

Shop ISO NNU6026 cylindrical roller bearings huge online discount inventory. and 9x24x7 Size (mm) Import machinery parts your car needs 9 Bore Diameter (mm) with Free Shipping and Free Extended Warranty.

Size (mm)	9x24x7
Bore Diameter (mm)	9
Outer Diameter (mm)	24
Width (mm)	7
d	9 mm
D	24 mm
B	7 mm
C	7 mm
r min.	0,3 mm
da min.	11 mm
da max	13,1 mm
Da max.	22 mm
ra max.	0,3 mm
Basic dynamic load rating (C)	3,4 kN
Basic static load rating (C0)	1,45 kN
(Grease) Lubrication Speed	31 000 r/min
Inventory	2.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.018
EAN	4547359010640

Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	9MM Bore; 24MM Outside Diameter; 7MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	609ZZ
Weight / LBS	0.0314
Outside Diameter	0.945 Inch   24 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Bore	0.354 Inch   9 Millimeter
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	9 mm
precision rating:	ISO Class 0
outside diameter:	24 mm
finish/coating:	Uncoated
overall width:	7 mm

bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	7 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	7 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	31000 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	36000 RPM
dynamic load capacity:	3400 N
series:	Micro
static load capacity:	1450 N
manufacturer product page:	<a href="#">Click here</a>