

ISO NP208 cylindrical roller bearings

Request A Quote For Your Special ISO NP208 cylindrical roller bearings Cylindrical Bore Bore Type Needs Today! Free Quotes. ISO 9001 certified.

| | |
|----------------------------|---------------------------------|
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Enclosure | Snap Ring Groove with Snap Ring |
| Weight | 0.024 kg |
| d | 12 mm |
| D | 28 mm |
| B | 8 mm |
| Fillet Radius/Chamfer | 0.3 mm |
| r1 | 0.3 mm |
| Snap Ring Width | 0.9 mm |
| Snap Ring Outside Diameter | 31 mm |
| D1 (max) | 26.7 mm |
| a (max) | 1.4 mm |
| b (min) | 0.9 mm |
| Dynamic Load Rating | 5,100 N |
| Static Load Rating | 2,390 N |
| Limiting Speed – Grease | 28,000 rpm |
| Limiting Speed – Oil | 32,000 rpm |
| Factor fo | 13.5 |
| Radial Clearance | 0.011 to 0.025 mm |
| da (min) | 14 mm |
| Da (max) | 26 mm |

| | |
|----------|---------|
| Dx (min) | 31.5 mm |
| ra (max) | 0.3 mm |
| Cy (max) | 1.9 mm |