

ISO NP2222 cylindrical roller bearings

ISO NP2222 cylindrical roller bearings SKF Manufacturer Name SEARCH – Whether it's agriculture or N/A Minimum Buy Quantity construction equipment your working on, 0.0 Inventory Has the you need.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.254
EAN	7316577722058
Product Group	B04144
Roller Surface Profile	Flat
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing – Double Row
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Full Complement With Flanged Inner Ring Labyrinth Seal
Long Description	20MM Bore; 47MM Roller Diameter; 24MM Roller Width; Flat Roller; Yoke Type; Sealed; Cylindrical Roll
UNSPSC	31171530
Harmonized Tariff Code	8482.50.00.00

Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NUTR 20 X
Weight / LBS	0.551
Roller Diameter	1.85 Inch 47 Millimeter
Roller Width	0.945 Inch 24 Millimeter
d	20 mm
roller diameter:	47 mm
radial dynamic load capacity:	28.6 kN
roller width:	24 mm
radial static load capacity:	33.5 kN
bore diameter:	20 mm
roller material:	Steel
roller shape:	Flat
maximum rpm:	3800 rpm
bearing element:	Cylindrical Rollers
finish/coating:	Uncoated
overall width:	25 mm
manufacturer catalog:	Click here
closure type:	Sealed
series:	NUTR
operating temperature range:	300 °F
manufacturer upc number:	7316577722058
D	47 mm
C	24 mm
B	25 mm
d1	27 mm
r1,2 min.	1 mm
r, r3,4 min.	0.5 mm

Basic dynamic load rating C	28.6 kN
Basic static load rating C ₀	33.5 kN
Fatigue load limit P _u	3.9 kN
Maximum dynamic radial loads F _r max.	17.6 kN
Maximum static radial loads F _{0r} max.	25 kN
Limiting speed	3800 r/min
Mass support roller	0.24 kg