

ISO NP230 cylindrical roller bearings

Find the discount ISO NP230 cylindrical roller bearings online you need . We offer ... If you check out our large selection of ISO NP230 cylindrical roller bearings 125 Outer Diameter (mm) once . 80x125x22 Size (mm)

| | |
|-------------------------------|-------------|
| Size (mm) | 80x125x22 |
| Bore Diameter (mm) | 80 |
| Outer Diameter (mm) | 125 |
| Width (mm) | 22 |
| d | 80 mm |
| D | 125 mm |
| B | 22 mm |
| C | 22 mm |
| Angle (α) | 25 ° |
| a | 40,5 mm |
| r min. | 1,1 mm |
| r1 min. | 0,6 mm |
| da min. | 87 mm |
| db min | 87 mm |
| ra max. | 1 mm |
| Weight | 0,994 Kg |
| Basic dynamic load rating (C) | 53,5 kN |
| Basic static load rating (C0) | 50,5 kN |
| (Grease) Lubrication Speed | 5 500 r/min |
| Contact angle α | 30 ° |
| rs min | 1.1 mm |

| | |
|---|---------------|
| r1s min | 0.6 mm |
| Mass | 0.99 kg |
| Dynamic load, C | 53.5 kN |
| Static load, C0 | 50.5 kN |
| Fatigue limit load, Cu | 2.27 kN |
| Nlim (oil) | 7,300 rpm |
| Nlim (grease) | 5,500 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.44 Hz |
| Characteristic rolling element frequency, BSF | 7.5 Hz |
| Characteristic outer ring frequency, BPF0 | 8.86 Hz |
| Characteristic inner ring frequency, BRFI | 11.14 Hz |
| da min | 87 mm |
| Da max | 118 mm |
| Db max | 120.5 mm |
| r1a max | 0.6 mm |
| ra max | 1 mm |
| Inventory | 1.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.974 |
| EAN | 4547359433265 |
| Product Group | B00308 |
| Enclosure | Open |
| Flush Ground | No |
| Rolling Element | Ball Bearing |

| | |
|---------------------------------|--|
| Number of Rows of Balls | Single Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 30 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Inch – Metric | Metric |
| Long Description | 80MM Bore; 125MM Outside Diameter; 22MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ba |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer Item Number | 7016 |
| Bore | 3.15 Inch 80 Millimeter |
| Width | 0.866 Inch 22 Millimeter |
| Outside Diameter | 4.921 Inch 125 Millimeter |