

# ISO NU1064 cylindrical roller bearings

YOU'LL 34.988×59.974×15.875 Size (mm) FIND 59,974 Outer Diameter (mm) AN 34,988 Bore Diameter (mm) EXTENSIVE SELECTION OF ISO NU1064 cylindrical roller bearings FOR SALE.

|                     |                      |
|---------------------|----------------------|
| Size (mm)           | 34.988×59.974×15.875 |
| Bore Diameter (mm)  | 34,988               |
| Outer Diameter (mm) | 59,974               |
| Width (mm)          | 15,875               |
| d                   | 34,988 mm            |
| D                   | 59,974 mm            |
| T                   | 15,875 mm            |
| a                   | 13,4 mm              |
| B                   | 16,764 mm            |
| C                   | 11,938 mm            |
| Ca min              | 3 mm                 |
| Cb min              | 4 mm                 |
| Da min              | 53 mm                |
| Db min              | 56 mm                |
| d1                  | 48,8 mm              |
| da max              | 39 mm                |
| db min              | 45,5 mm              |
| r1, 2 min           | 3,6 mm               |
| r3, 4 min           | 1,3 mm               |
| ra max              | 3,6 mm               |
| rb max              | 1,3 mm               |
| m                   | 0,179 kg / Weight    |

|     |  |
|-----|--|
| Cr  | 34000 N / Dynamic load rating (radial) |
| C0r | 44500 N                                |
| e   | 0,42                                   |
| Y   | 1,44                                   |
| Y0  | 0,79                                   |
| Cur | 5000 N / Fatigue limit load, radial    |
| nG  | 12400 1/min / Limiting speed           |