

ISO NUP1072 cylindrical roller bearings

Request A Quote For Your Mounted Bearing Engineering Group Special ISO NUP1072 cylindrical roller bearings Needs Today! Free Quotes. ISO Metric Shaft Size Type 9001 certified.

| | |
|-------------------------|-------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 45 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QMF09J045SB |
| Locking Style | Eccentric |
| Weight | 11.0 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450031493 |
| Dimension BC | 5.5 in |
| Dimension C | 2.63 in |
| Dimension D | 4.250 in |
| Dimension E | 3.89 in |
| Dimension F | 5.13 in |
| Dimension H | 0.88 in |
| Dimension J (Bolt Size) | 0.5 in |
| Dimension K | 0.99 in |
| Dimension L Exp | 3.21 in |
| Dimension L Fix | 3.13 in |
| Dimension M | 1.88 in |
| Dimension N | 2.500 in |
| Dimension R | 0.25 in |
| Dimension S | 2.87 in |

| | |
|-------------------------------------|-----------|
| C0 – Static Load | 24200 lb |
| C – Dynamic Load (Basic) | 24500 lb |
| e – Geometry Factor | 0.27 |
| Y1 – Geometry Factor | 2.5 |
| Y2 – Geometry Factor | 3.72 |
| Oil Lubrication – M/N Seal | 2700 rpm |
| Oil Lubrication – T Seal | 4500 rpm |
| Oil Lubrication – B/C/O Seal | 1950 rpm |
| Grease Lubrication – M/N Seal | 2700 rpm |
| Grease Lubrication – T Seal | 4000 rpm |
| Grease Lubrication – B/C/O Seal | 1950 rpm |
| Float | 0.050 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0014 |
| Eng Internal Radial Clearance – Max | 0.0022 |
| Pre Install Clearance Min | 0.0014 in |
| Pre Install Clearance Max | 0.0022 in |