

ISO NUP3219 cylindrical roller bearings

offers a ISO NUP3219 cylindrical roller bearings selection of Genuine 55 mm D at Wholesale Prices. 20 mm C We are a ISO NUP3219 cylindrical roller bearings Certified 40 mm Fw Parts Retailer

Fw	40 mm
D	55 mm
C	20 mm
E	47 mm
rs min	0.3 mm
Dw	3.5 mm
Lw	15.8 mm
Lubrication hole on outer ring	Non/No
Radial clearance class	CN
Precision class	P0
Mass	0.14 kg
Cr	31 kN
C0r	51.5 kN
Nlim (grease)	6,500 rpm
Nlim (oil)	10,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	12.35 Hz
Characteristic outer ring frequency, BPF0	11.03 Hz
Characteristic inner ring frequency, BRFI	12.97 Hz

db	46.2 mm
Da max	53 mm
Db	40.6 mm
ras max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.158
Product Group	B04144