

ISO NUP3884 cylindrical roller bearings

Request A Quote For Your Special ISO NUP3884 cylindrical roller bearings Needs Today! 55 Bore Diameter (mm) Free Quotes. ISO 55x68x35 Size (mm) 9001 certified.

Size (mm)	55x68x35
Bore Diameter (mm)	55
Outer Diameter (mm)	68
Width (mm)	35
Fw	55 mm
D	68 mm
C	35 mm
r min.	0,6 mm
Da max.	64 mm
ra max.	0,6 mm
Weight	0,267 Kg
Basic dynamic load rating (C)	54 kN
Basic static load rating (C0)	118 kN
(Grease) Lubrication Speed	5000 r/min
rs min	0.6 mm
Dw	3.5 mm
Lw	27.8 mm
Lubrication hole on outer ring	Oui/Yes
k	3 mm
Radial clearance class	CN
Precision class	P0
Mass	0.26 kg

Cr	54 kN
C0r	118 kN
Nlim (grease)	5,000 rpm
Nlim (oil)	7,500 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	16.65 Hz
Characteristic outer ring frequency, BPF0	14.57 Hz
Characteristic inner ring frequency, BRFI	16.43 Hz
Da max	64 mm
ras max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.278
Product Group	B04144