ISO SIL 10 plain bearings

Advance ISO SIL 10 plain bearings is your source for quality and accessories. shop online Two-Bolt Base mounting: for home delivery or pick up in one of our 10000 .

mounting:Two-Bolt Basefinish/coating:Black Oxided2.4375 inB2.38 inbore type:Roundradial dynamic load capacity:11791 lbbase to bore centerline:2.7500 inradial static load capacity:8100 lbduty type:Normal Dutybase width:2.37 inhousing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Scott/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 inverall height:5.4000 in		
d2.4375 inB2.38 inbore type:Roundradial dynamic load capacity:11791 lbbase to bore centerline:2.7500 inradial static load capacity:8100 lbduty type:Normal Dutybase width:2.37 inhousing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 inUL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 certified	mounting:	Two-Bolt Base
B2.38 inbore type:Roundradial dynamic load capacity:11791 lbbase to bore centerline:2.7500 inradial static load capacity:8100 lbduty type:Normal Dutybase width:2.37 inhousing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Schatzseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 inUL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 certified	finish/coating:	Black Oxide
bore type:Roundradial dynamic load capacity:11791 lbbase to bore centerline:2.7500 inradial static load capacity:8100 lbduty type:Normal Dutybase width:2.37 inhousing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 certified	d	2.4375 in
radial dynamic load capacity: 11791 lb base to bore centerline: 2.7500 in radial static load capacity: 8100 lb duty type: Normal Duty base width: 2.37 in housing material: Cast Iron D 6.88 to 7.94 in locking device: Concentric Collar lubrication type: Lubrication Fitting seal type: Contact/Lip series: 212 expansion type: Non-Expansion Bearing (Fixed) manufacturer catalog number: 128451 overall length: 9.5000 in standards met: UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	В	2.38 in
base to bore centerline: 2.7500 in radial static load capacity: 8100 lb duty type: Normal Duty base width: 2.37 in housing material: Cast Iron D 6.88 to 7.94 in locking device: Concentric Collar lubrication type: Lubrication Fitting seal type: Contact/Lip series: 212 expansion type: Non-Expansion Bearing (Fixed) manufacturer catalog number: 128451 overall length: 9.5000 in standards met: UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	bore type:	Round
radial static load capacity: 8100 lb duty type: Normal Duty base width: 2.37 in housing material: Cast Iron D 6.88 to 7.94 in locking device: Concentric Collar lubrication type: Lubrication Fitting seal type: Contact/Lip series: 212 expansion type: Non-Expansion Bearing (Fixed) manufacturer catalog number: 128451 overall length: 9.5000 in standards met: UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	radial dynamic load capacity:	11791 lb
duty type:Normal Dutybase width:2.37 inhousing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	base to bore centerline:	2.7500 in
base width:2.37 inhousing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	radial static load capacity:	8100 lb
housing material:Cast IronD6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	duty type:	Normal Duty
D6.88 to 7.94 inlocking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	base width:	2.37 in
locking device:Concentric Collarlubrication type:Lubrication Fittingseal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	housing material:	Cast Iron
Lubrication type:Lubrication Fittingseal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	D	6.88 to 7.94 in
seal type:Contact/Lipseries:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	locking device:	Concentric Collar
series:212expansion type:Non-Expansion Bearing (Fixed)manufacturer catalog number:128451overall length:9.5000 instandards met:UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	lubrication type:	Lubrication Fitting
expansion type: Non-Expansion Bearing (Fixed) manufacturer catalog number: 128451 overall length: 9.5000 in standards met: UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified	seal type:	Contact/Lip
<pre>manufacturer catalog number: 128451 overall length: 9.5000 in standards met: UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ISO 9002 Certified</pre>	series:	212
overall length: 9.5000 in UL, AFBMA, AGMA, ASMMA, BSA, Standards met: CMA, MPTA, PTDA, ISO 9002 Certified	expansion type:	Non-Expansion Bearing (Fixed)
UL, AFBMA, AGMA, ASMMA, BSA, standards met: CMA, MPTA, PTDA, ISO 9002 Certified	manufacturer catalog number:	128451
standards met: CMA, MPTA, PTDA, ISO 9002 Certified	overall length:	9.5000 in
overall height: 5.4000 in	standards met:	CMA, MPTA, PTDA, ISO 9002
	overall height:	5.4000 in