

# ISO TM2/25,5 deep groove ball bearings

ISO TM2/25,5 deep groove ball bearings Warehouse offers car parts and car accessories. We sell discount online as well as 17x35x10 Size (mm) cheap 17 Bore Diameter (mm) machinery parts.

|                               |               |
|-------------------------------|---------------|
| Size (mm)                     | 17x35x10      |
| Bore Diameter (mm)            | 17            |
| Outer Diameter (mm)           | 35            |
| Width (mm)                    | 10            |
| d                             | 17 mm         |
| D                             | 35 mm         |
| B                             | 10 mm         |
| C                             | 10 mm         |
| d1                            | 23 mm         |
| r1 min.                       | 0,3 mm        |
| r2 min.                       | 0,3 mm        |
| D2                            | 31,2 mm       |
| Weight                        | 0,038 Kg      |
| Temperature –                 | 30 to +250 °  |
| Basic static load rating (C0) | 3,25 kN       |
| Inventory                     | 0.0           |
| Manufacturer Name             | SKF           |
| Minimum Buy Quantity          | N/A           |
| Weight / Kilogram             | 0.043         |
| EAN                           | 7316571110981 |
| Product Group                 | B00308        |

|                                 |  |
|---------------------------------|--|
| Enclosure                       | Open   |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Rolling Element                 | Ball Bearing   |
| Snap Ring                       | No   |
| Internal Special Features       | Polyalkylene Glycol/Graphite Mixture Filled  |
| Cage Material                   | Steel  |
| Internal Clearance              | C0-Medium  |
| Inch – Metric                   | Metric   |
| Long Description                | 17MM Bore; 35MM Outside Diameter; 10MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fil |
| Other Features                  | Deep Groove   Extreme Temperature Variant  |
| UNSPSC                          | 31171504   |
| Harmonized Tariff Code          | 8482.10.50.68  |
| Noun                            | Bearing  |
| Keyword String                  | Ball   |
| Manufacturer Item Number        | 6003/VA201   |
| Weight / LBS                    | 0.094  |
| Outer Race Width                | 0.394 Inch   10 Millimeter   |
| Outside Diameter                | 1.378 Inch   35 Millimeter   |
| Inner Race Width                | 0 Inch   0 Millimeter  |
| Bore                            | 0.669 Inch   17 Millimeter   |
| bore diameter:                  | 17 mm  |
| static load capacity:           | 3.25 kN  |
| outside diameter:               | 35 mm  |
| precision rating:               | Not Rated  |

|                              |  |
|------------------------------|--|
| overall width:               | 10 mm                                    |
| finish/coating:              | Uncoated                                 |
| bore type:                   | Round                                    |
| cage material:               | Steel                                    |
| closure type:                | Open                                     |
| outer ring width:            | 10 mm                                    |
| row type & fill slot:        | Single Row Non-Fill Slot                 |
| fillet radius:               | 0.3 mm                                   |
| snap ring included:          | Without Snap Ring                        |
| maximum rpm:                 | 340 RPM                                  |
| internal clearance:          | C0                                       |
| series:                      | 60                                       |
| operating temperature range: | -20 to +480 °F                           |
| resistance features:         | Corrosion Resistant, Extreme Temperature |
| d1 ≈                         | 23 mm                                    |
| D2 ≈                         | 31.2 mm                                  |
| r1,2 min.                    | 0.3 mm                                   |
| da min.                      | 19 mm                                    |
| Da max.                      | 33 mm                                    |
| ra max.                      | 0.3 mm                                   |
| Basic dynamic load rating C  | 6.37 kN                                  |
| Basic static load rating C0  | 3.25 kN                                  |
| Limiting speed               | 340 r/min                                |
| Limiting temperature T max.  | 250 °C                                   |
| Mass bearing                 | 0.038 kg                                 |