

# ISO UCFCX07 bearing units

With over 10170 full-service stores, our ISO UCFCX07 bearing units inventory is extensive and our parts are priced right. 68,263 mm d within 24 hours. This helps you maximize your productivity by 68,263 Bore Diameter (mm) saving time and your hard-earned dollars.

Bore Diameter (mm)	68,263
d	68,263 mm
s1	42.9 mm
A	65 mm
A1	44 mm
B	68,3 mm
G	20 mm
H	149 mm
H1	76.2 mm
H2	29 mm
J	203 mm
L	257 mm
N	35 mm
N1	22 mm
Weight	5,7 Kg
Basic dynamic load rating (C)	57,2 kN
Basic static load rating (C0)	40 kN
Fatigue load limit (Pu)	1,7
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	5.685

EAN	7316577755704
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	YAR 213-211-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row   Standard Duty   Wide Inner Race   Y Bearing   Has Flinger
Long Description	2 Bolt Pillow Block; 2-11/16" Bore; 3" Base to Center Height; Set Screw Mount; Ball Bearin
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 2.11/16 TF
Weight / LBS	13.5
Base to Center Height	3 Inch   76.2 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
Bolt Spacing Minimum	7.469 Inch   189.713Millimeter

Bolt Spacing Maximum	8.5 Inch   215.9Millimeter
Nominal Bolt Center to Center	8 Inch   203 Millimeter
Length Thru Bore	2.688 Inch   68.275 Millimeter
Bore	2.688 Inch   68.275 Millimeter
Housing material	Cast iron
A5	39 mm
B4	10 mm
J max.	216 mm
J min.	190 mm
RG	1/4-28 UNF
R1	5.5 mm
Rα	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	238 mm
J7	22.5 mm
N4	4 mm
Basic dynamic load rating C	57.2 kN
Basic static load rating C0	40 kN
Fatigue load limit Pu	1.7 kN
Limiting speed	3000 r/min
Mass bearing unit	5.3 kg
Thread grub screw G2	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	20 mm

Recommended diameter for attachment bolts, inch G	0.75 in
Housing	SY 513 M
Bearing	YAR 213-211-2F
End cover	ECY 213